

# EVERCOAT®

Every time, Everywhere

## SLICK SAND

104708 & 104709



### High build polyester spray filler

A high-solids, extra high-build polyester based Spray Filler featuring Incredible build; 200-300 microns in just one coat! The ideal coating to provide a flat, even surface on the most uneven of substrates. The USA's favourite primer filler for customizing and restoration jobs.

Formulated with a high quality polyester resin SLICK SAND's finish is super smooth and does not shrink. It requires minimal sanding and finishing before being over-coated with your choice of coating. More akin to high quality gel coat than a standard polyester spray filler.

SLICK SAND is ideal for a variety of substrates including steel, aluminium, wood, fiberglass, SMC, DMC, BMC and body filler. This makes it the first choice of product for:

- Fleet work
- Commercial work
- Restoration jobs
- Customizing
- Wood preparation
- Mold & plug making
- Marine applications

SLICK SAND has it covered!

### TECHNICAL DATA

		Part no.	Size	Packing	Weight
Appearance	Gray liquid				
VOC	Packaged (305 g/L)	104708	.946L/can	6 units/case	9.5 kg/case
	Applied (206 g/L)	104709	3.78L/can	4 units/case	22.7 kg/case
Dry-Film-thickness (DFT)	4.0 – 6.0 mils per coat				
Solids by Volume	57-62%				
Solids by Weight	71-74%				
Mix Ratio	50:1				

## EVERCOAT®

Evercoat | a division of Illinois Tool Works Inc. | Unit 7 Westwood House | Westwood Way | Westwood Business Park | Coventry | CV4 8HS | United Kingdom  
T: +44(0) 24 7647 4069 | F: +44(0) 24 7647 1213

Crta. Urnieta s/n | 20140 - ANDOAIN | SPAIN | Phone: 34-943-410-402 | © 2015 Evercoat

[evercoat.com](http://evercoat.com)