

## A - G Direct Drive Compressors

Model No. **SEE BELOW**

All models feature aluminium cylinder heads with cast iron cylinders giving added resistance to wear over time. Suitable for general purpose and workshop applications. All feature a single cylinder pump, except for Model No's. SAC5030VE and SAC10030VE which are fitted with a V-Twin pump for added performance. Pump heads are directly coupled to a heavy-duty induction motor with copper windings for improved operation and longer working life. Welded tank complies with latest European standards. Fitted with fully automatic pressure cut-out switch with twin gauges displaying tank and working pressures. 230V Models are fitted with 3-pin plug. Model No's SAC2420EPK and SAC5020EPK are supplied with 4pc Air Accessory Kit.



Copper wound motors provide longer lasting performance over aluminium wound motors.



	<b>A</b>	<b>B F</b>	<b>C G</b>	<b>D</b>	<b>E</b>
<b>Model No:</b>	SAC0610E	SAC2420E*	SAC5020E*	SAC5030VE	SAC10030VE
<b>Motor Output:</b>	1hp	2hp	2hp	3hp	3hp
<b>Supply:</b>	230V	230V	230V	230V	230V
<b>Phase:</b>	1ph	1ph	1ph	1ph	1ph
<b>Minimum Rated Supply:</b>	13A	13A	13A	13A	13A
<b>Air Displacement cfm(L/min):</b>	4(113)	6.8(193)	6.8(193)	12.6(357)	12.6(357)
<b>Maximum Free Air Delivery cfm(L/min):</b>	2.7(76)	4.6(130)	4.6(130)	8.8(249)	8.8(249)
<b>Maximum Pressure:</b>	116psi(8bar)	116psi(8bar)	116psi(8bar)	116psi(8bar)	116psi(8bar)
<b>Receiver Capacity:</b>	6L	24L	50L	50L	100L
<b>Outlet:</b>	Quick Release Coupling				
<b>Size (W x D x H):</b>	400 x 175 x 430mm	600 x 290 x 585mm	650 x 390 x 669mm	695 x 375 x 630mm	890 x 450 x 760mm
<b>Compressor Weight:</b>	14.5kg	26.5kg	29kg	39kg	52kg

\* For Accessory Kit version add PK to part number