

QUARTZ

15050

1K Plastic Primer

TDS No.: 4450 EN // TDS Date: V1-25.10.2012

| | |
|----------------------------|--|
| Product | 1K Plastic Primer |
| Colour | Transparent |
| Product description | <p>Good adhesion on all plastic interior and exterior car parts, including bumpers, mirrors and tuning parts.</p> <p>Quick-drying, high elasticity, high yield.</p> <p>Can applied directly as a primer.</p> <p>Recoatable with 1K and 2K Primer Filler, RAL-acrylic topcoat and pre-fill base paints.</p> |
| Use for | Most car and trucks interior and exterior plastic parts. |
| Substrate | PP, PP/EPDM, ABS, SAN, PC, PA, PUR-RIM, R-TPU, PPO, PBT, PUR flexible foam, UP-GF plastics |
| Base of binder | Polyolefin resin |
| Application | <p>Apply one light coat</p> <p>Dry for 10 minutes at 20 °C; recoatable after 10 minutes at 20 °C</p> <p>The drying time depends on ambient temperature, air humidity and the applied layer thickness</p> |
| Efficiency | <p>400ml are sufficient for approx. 3 - 4 m².</p> <p>Depending on the substrate, colour and application thickness</p> |
| Size | 400 ml |
| VOC | 276,4 g |
| Storage stability | <p>10 years</p> <p>Store in a dry place and away from sunlight (10 °C-25 °C). Maximum air humidity 60 %.</p> |
| Flashpoint | > +23 °C |

Information given in this sheet represent the best of our knowledge. Please verify before use if this product is suitable for your application.