

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 05.12.2016

Version number 1

Revision: 05.12.2016

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name:** ProXL® UNIVERSAL ADHESION PROMOTER 500 ML
- **Article number:** PROGRIP
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**  
 SU21 Consumer uses: Private households / general public / consumers  
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** PC9a Coatings and paints, thinners, paint removers
- **Process category**  
 PROC7 Industrial spraying  
 PROC11 Non industrial spraying
- **Environmental release category**  
 ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)  
 ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)
- **Application of the substance / the mixture** Spray varnish
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
 ProXL  
 Second Avenue  
 Chatham  
 Kent  
 ME4 5AU  
 Tel: +44 (0)1634 823900  
 Fax: +44 (0)1634 823909  
 Email: info@pro-xl.co.uk
- **Further information obtainable from:** Department Product Safety
- **1.4 Emergency telephone number:** Tel: +44(0) 1634 823900 (08.00 / 17.00)

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
 The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.12.2016

Version number 1

Revision: 05.12.2016

Trade name: ProXL® UNIVERSAL ADHESION PROMOTER 500 ML

(Contd. of page 1)

## · Hazard pictograms



GHS02 GHS07

· Signal word *Danger*

## · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

## · Precautionary statements

P102 Keep out of reach of children.

P260 Do not breathe spray.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

## · 2.3 Other hazards

## · Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

## · 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

## · Dangerous components:

CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether Flam. Gas 1, H220 Press. Gas C, H280	50-75%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32-xxxx	xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	12.5-20%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	5-10%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35-xxxx	ethylbenzene Flam. Liq. 2, H225 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H332 Aquatic Chronic 3, H412	5-10%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

## · 4.1 Description of first aid measures

## · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 05.12.2016

Version number 1

Revision: 05.12.2016

**Trade name: ProXL® UNIVERSAL ADHESION PROMOTER 500 ML**

(Contd. of page 2)

- **After inhalation:**  
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation  
Keep away from ignition sources.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
No special measures required.  
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 05.12.2016

Version number 1

Revision: 05.12.2016

**Trade name: ProXL® UNIVERSAL ADHESION PROMOTER 500 ML**

(Contd. of page 3)

- **Further information about storage conditions:** Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**115-10-6 dimethyl ether**

WEL Short-term value: 958 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 766 mg/m<sup>3</sup>, 400 ppm

**1330-20-7 xylene**

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 220 mg/m<sup>3</sup>, 50 ppm  
Sk, BMGV

**108-65-6 2-methoxy-1-methylethyl acetate**

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 274 mg/m<sup>3</sup>, 50 ppm  
Sk

**100-41-4 ethylbenzene**

WEL Short-term value: 552 mg/m<sup>3</sup>, 125 ppm  
Long-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Sk

· **Ingredients with biological limit values:**

**1330-20-7 xylene**

BMGV 650 mmol/mol creatinine  
Medium: urine  
Sampling time: post shift  
Parameter: methyl hippuric acid

- **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 05.12.2016

Version number 1

Revision: 05.12.2016

Trade name: ProXL® UNIVERSAL ADHESION PROMOTER 500 ML

(Contd. of page 4)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· <b>Form:</b>	Aerosol
· <b>Colour:</b>	Different according to colouring
· <b>Odour:</b>	Solvent-like
· <b>Odour threshold:</b>	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· <b>Melting point/Melting range:</b>	Undetermined.
· <b>Boiling point/Boiling range:</b>	Not applicable, as aerosol.

· **Flash point:** <0 °C (<32 °F)  
Not applicable, as aerosol.

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 240 °C (464 °F)

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

· <b>Lower:</b>	1.0 Vol %
· <b>Upper:</b>	26.2 Vol %

· **Vapour pressure at 20 °C (68 °F):** 4000 hPa (3000 mm Hg)

· **Density at 20 °C (68 °F):** 0.762 g/cm<sup>3</sup> (6.359 lbs/gal)

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not applicable.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

· <b>Dynamic:</b>	Not determined.
· <b>Kinematic:</b>	Not determined.

· **Solvent content:**

· <b>Organic solvents:</b>	88.0 %
· <b>EU-VOC:</b>	670.6 g/l
· <b>EU-VOC in %:</b>	88.00 %

(Contd. on page 6)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 05.12.2016

Version number 1

Revision: 05.12.2016

Trade name: ProXL® UNIVERSAL ADHESION PROMOTER 500 ML

(Contd. of page 5)

- |                                |  |
|--------------------------------|--|
| · <b>Solids content:</b>       | 12.0 %                                     |
| · <b>9.2 Other information</b> | No further relevant information available. |

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

**115-10-6 dimethyl ether**

Inhalative	LC50 / 4 h	308 mg/m <sup>3</sup> (rat)
------------	------------	-----------------------------

**1330-20-7 xylene**

Oral	LD50	3523 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	22.1 mg/m <sup>3</sup> (rat)

**108-65-6 2-methoxy-1-methylethyl acetate**

Oral	LD50	8532 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	35.7 mg/m <sup>3</sup> (rat)

**100-41-4 ethylbenzene**

Oral	LD50	3500 mg/kg (rat)
Dermal	LD50	17800 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

GB

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 05.12.2016

Version number 1

Revision: 05.12.2016

Trade name: ProXL® UNIVERSAL ADHESION PROMOTER 500 ML

(Contd. of page 6)

### SECTION 12: Ecological information

#### · 12.1 Toxicity

##### · Aquatic toxicity:

##### **115-10-6 dimethyl ether**

EC50 / 48 h	>4000 mg/l (daphnia magna)
-------------	----------------------------

##### **1330-20-7 xylene**

EC50 / 48 h	7.4 mg/l (daphnia magna)
-------------	--------------------------

LC50 / 96 h	13.5 mg/l (fish)
-------------	------------------

##### **108-65-6 2-methoxy-1-methylethyl acetate**

EC50	408 mg/l (daphnia magna)
------	--------------------------

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

##### · Ecotoxicological effects:

· **Remark:** Harmful to fish

##### · Additional ecological information:

##### · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

##### · 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

#### · 13.1 Waste treatment methods

##### · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

##### · European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
-----------	---

15 01 04	metallic packaging
----------	--------------------

##### · Uncleaned packaging:

· **Recommendation:** Non contaminated packagings may be recycled.

### SECTION 14: Transport information

#### · 14.1 UN-Number

· **ADR, IMDG, IATA**

UN1950

#### · 14.2 UN proper shipping name

· **ADR**

1950 AEROSOLS

· **IMDG**

AEROSOLS

· **IATA**

AEROSOLS, flammable

(Contd. on page 8)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 05.12.2016

Version number 1

Revision: 05.12.2016

Trade name: ProXL® UNIVERSAL ADHESION PROMOTER 500 ML

(Contd. of page 7)

## · 14.3 Transport hazard class(es)

## · ADR



· Class 2 5F Gases.  
· Label 2.1

## · IMDG, IATA



· Class 2.1  
· Label 2.1

## · 14.4 Packing group

· ADR, IMDG, IATA Void

## · 14.5 Environmental hazards:

· Marine pollutant: No

## · 14.6 Special precautions for user

· Danger code (Kemler): -  
· EMS Number: F-D,S-U  
· Stowage Code SW1 Protected from sources of heat.  
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.  
· Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

## · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

## · Transport/Additional information:

## · ADR

· Limited quantities (LQ) 1L  
· Excepted quantities (EQ) Code: E0  
Not permitted as Excepted Quantity  
· Transport category 2  
· Tunnel restriction code D

## · IMDG

· Limited quantities (LQ) 1L  
· Excepted quantities (EQ) Code: E0  
Not permitted as Excepted Quantity

## · UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

GB

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 05.12.2016

Version number 1

Revision: 05.12.2016

Trade name: ProXL® UNIVERSAL ADHESION PROMOTER 500 ML

(Contd. of page 8)

### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

- **Department issuing SDS:** R&D legislation and regulatory advisor

- **Contact:** QHSE Department

- **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Gas 1: Flammable gases – Category 1
- Aerosol 1: Aerosols – Category 1
- Press. Gas C: Gases under pressure – Compressed gas
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- **\* Data compared to the previous version altered.**